

AD-A082 882

ILC DOVER FREDERICA DE PROTECTIVE EQUIPMENT DIV
REDESIGNED PASS-THROUGH HEAT SEAL DIE.(U)
MAR 80 C R SANDY

F/6 13/8

DAAK11-79-C-0066

NL

UNCLASSIFIED

101
201-414




END

DATE

FILED

5-80

DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

LEVEL

2

Redesigned Pass-Through Heat Seal Die

DAAK11-79-C-0066

ADA U82882

Charles R. Sandy
Project Engineer
Protective Equipment Division
ILC DOVER
P.O. Box 266
Frederica, Delaware
19946

DTIC
ELECTE
APR 9 1980

28 March 1980

Final Report for Period 11 June 1979 -- 29 March 1980

Prepared For:

CDR, ARRADCOM
CML/Ballistics Procurement
APG (Edgewood Area), Maryland
21010

DCASR Philadelphia
P.O. Box 7730
Philadelphia, Pennsylvania
19101

This document has been approved
for public release and sale; its
distribution is unlimited.

The view, opinions, and/or findings contained in this report are those of the author and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.

DDC FILE COPY

80 4 4 032

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER DAAK11-79-C-0066-03	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Redesigned Pass-Through Heat Seal Die		5. TYPE OF REPORT & PERIOD COVERED Final Report - 11 Jun 79 - 29 Mar 80
7. AUTHOR(s) Charles R. Sandy, Project Engineer Protective Equipment, ILC DOVER		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS ILC DOVER P.O. Box 266 Frederica, Delaware 19946		8. CONTRACT OR GRANT NUMBER(s) DAAK11-79-C-0066
11. CONTROLLING OFFICE NAME AND ADDRESS CDR, ARRADCOM CML/Ballistics Procurement APG (Edgewood Area), Maryland 21010		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Task Order Number 3
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) DCASR Philadelphia P.O. Box 7730 Philadelphia, Pennsylvania 19101		12. REPORT DATE 28 March 1980
		13. NUMBER OF PAGES Page 1 of 4
		15. SECURITY CLASS. (of this Report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release: Distribution Unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Outergarment DPE, Demilitarization Protective Ensemble		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This task was authorized to redesign the heat seal tool that attaches the air inlet to the DPE Outergarment. The original tool had permitted electrical arcing between the inlet fitting and itself during the heat seal operation. The new tool eliminates this arcing and continues to make a heat sealed seam of equal strength.		

DD FORM 1473

EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

FOREWARD

The work reported herein was conducted by ILC DOVER, Frederica, Delaware, for ARRADCOM, CML/Ballistics Procurement, APG (Edgewood Area), Maryland in accordance with Contract DAAK11-79-C-0066, Task Order Number 3. Mr. Donald R. Cohee was the Program Manager for ILC DOVER. Mr. Wayne Davis was the Contract Monitor for the Chemical Systems Laboratory. This work was accomplished between 11 June 1979 and 29 March 1980.

This technical report has been reviewed and is approved.

Mr. David M. English, Chief
Combat Vehicle Section
Physical Protection Division
Chemical Systems Laboratory

Accession For	
NTIS GRA&I	
DDC TAB	
Unannounced	
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or special
A	

INTRODUCTION

This task was authorized to redesign the air inlet pass-through attachment die in order to eliminate the arcing between the die and the inlet fittings. The arcing occurs during the heat sealing operation when one of the inlet fittings comes in electrical contact with the inside wall of the die.

COMPLETED ACTIVITY

The following work was performed during the completion of this task order:

- (1) The die was redesigned to eliminate arcing by using nonconducting phenolic inserts on the walls of the cavity in the die. This simply involves enlargement of the cavity, to accommodate the inserts, leaving the same amount of space for the pass-through fitting. Other modifications were made to make the die more durable and easier to use.

These are as follows:

- (a) The lower die was made higher, giving the pass-through fittings clearance from the bottom platen, so that the operator does not have to pick up the entire block for each pass-through insertion. The top die was made slightly shorter so that the entire assembly (top die, pass-through, and lower die) can fit between the heat seal platens.
- (b) The lower die was changed to include a brass insert in the area where the pass-through is inserted. The brass is more durable than aluminum, and will be less damaged by the impact

of the fittings as the operator inserts them. Also, the inserts will be easier and less expensive to replace than a whole new die when the denting has become pronounced enough to affect the heat seal.

- (2) The redesigned die was fabricated, and the necessary drawings made. Seam samples made with the new tool were tested and found adequate per specification. ECP Number 80-0058-005 includes the tool drawings and seam sample test results.
- (3) All changes to the specification, tool drawings and test results have been submitted to CSL for approval. Refer to ECP Number 80-0058-005 for this documentation.

CONCLUSION

The redesigned pass-through heat seal die is now available for use in production of DPE Outergarments.